

SPECIFICATION FOR REFERENCE

CUSTOMER:	平台
CUSTOMER P.N.:	
MODEL NO.:	P30-Z3250R200-065X0-E
PRODUCT NO.:	SDXXX-E0
SAMPLE DATE:	2025-03-20

CUSTOMER AUTHORIZED SIGNATURE

--	--	--

Please return to us one copy of "SPECIFICATION FOR APPROVAL"
with you approved signature.

**ADD: MOSO Industrial Park, Nanshan District, Shenzhen, Guangdong
518108, P. R. China**

TEL: 86-755-27657000 27657555

P.C.: 518108

FAX: 86-755-27657908

E-mail:moso@mosopower.com

<http://www.mosopower.com>

MANUFACTURER AUTOGRAPH

Reviser	Confirm	Checked	Approval

---Table of Content---

1. SCOPE	4
1.1. Description.....	4
1.2. Green Requirements	4
1.3. Energy Efficiency Requirements	4
2. Input Characteristics.....	5
2.1. Input Voltage & Frequency.....	5
2.2. Input AC Current.....	5
2.3. Inrush Current (cold start).....	5
2.4. Averaged Efficiency	5
2.5. Energy Consumption.....	5
2.6. Power saving requirement.....	5
3. Output Characteristics.....	5
3.1. Static Output Characteristics <Vo & R+N>.....	5
3.2. Line/ Load Regulation.....	5
3.3. Turn - on Delay Time.....	6
3.4. Hold-up Time	6
3.5. Output Overshoot / Undershoot.....	6
3.6. Output Transient Response	6
4. Protection Requirements	6
4.1. Over Voltage Protection (auto-recovery)	6
4.2. Over Current Protection.....	6
4.3. Short Circuit Protection	7
5. Environment Requirements.....	7
5.1. Operating Temperature and Relative Humidity	7
5.2. Storage Temperature and Relative Humidity	7
5.3. Vibration.....	7
5.4. Drop in	7
6. Reliability Requirements	7
6.1. Burn-in.....	7
6.2. MTBF Qualification	7
6.3. E-caps lifetime	7
7. EMI/EMS Standards.....	7
7.1. EMI Standards	7
7.2. EMS Standards	7
8. Safety Standards	8
8.1. Dielectric Strength(Hi-pot).....	8
8.2. Leakage Current.....	8

8.3. Insulation Resistance	9
8.4. Regulatory Standards.....	9
9. Mechanical Outline Drawing.....	10
10. I/O Marking Drawing.....	11
11. Package Drawing.....	13

1. SCOPE

The document detail the electrical, mechanical and environmental specifications of a Fast Charger, the Fast Charger provide 65W continuous output power.

The Fast Charger shall meet the HSF requirement.

1.1.Description

- | | |
|---|--|
| <input type="checkbox"/> SMPS Adaptor(Wall mount) | <input type="checkbox"/> SMPS Adaptor(Desk-top) |
| <input type="checkbox"/> Open Frame | <input type="checkbox"/> SMPS Unit (With Case) |
| <input type="checkbox"/> PD Adaptor(Wall mount) | <input type="checkbox"/> Others |
| <input type="checkbox"/> Others | <input checked="" type="checkbox"/> PD Adaptor(Desk-top) |

1.2.Green Requirements

- RoHS:2011/65/EU & (EU) 2015/863;
- REACH:1907/2006/EC;
- Halogen-free:IEC 61249-2-21;
- CA Prop 65;
- POPs:(EU)2023/1608;
- PAHs: 2005/69/EC;
- Packaging Directive:94/62/EC;
- US EPA Toxic Substances Control Act (TSCA);
- MOSO Environmental standards: WI-QM006-G;
- Others

1.3.Energy Efficiency Requirements

No.	Country	Energy efficiency abbreviation	Whether it meets the requirements/(YES/ <input checked="" type="checkbox"/> , NO/ <input type="checkbox"/>)
1	USA	DoE VI	<input checked="" type="checkbox"/>
2		CEC	<input type="checkbox"/>
3	Canada	NRCan	<input type="checkbox"/>
4	Australia/New Zealand	GEMS	<input type="checkbox"/>
5	Europe	Erp VI	<input type="checkbox"/>
6		CoC V5 Tier 2	<input type="checkbox"/>
7	South Korea	KMEPS	<input type="checkbox"/>
8	Mexico	MEPS	<input type="checkbox"/>
9	Byelorussia	MEPS	<input type="checkbox"/>

2. Input Characteristics

2.1. Input Voltage & Frequency

The range of input voltage is from 90Vac to 264Vac single phase.

	Minimum	Nominal	Maximum
Input Voltage	90Vac	100Vac~240Vac	264Vac
Input Frequency	47Hz	50Hz/60Hz	63Hz

2.2. Input AC Current

1.7A max. @ 100-240Vac input & Full load

2.3. Inrush Current (cold start)

No damage

2.4. Averaged Efficiency

5V3A: 81.84% min. @ 115V/230Vac input (@25%, 50%, 75% and 100% of max load)

9V3A: 87.3% min. @ 115V/230Vac input (@25%, 50%, 75% and 100% of max load)

12V3A: 88.30% min. @ 115V/230Vac input (@25%, 50%, 75% and 100% of max load)

15V3A: 88.85% min. @ 115V/230Vac input (@25%, 50%, 75% and 100% of max load)

20V3.25A: 89% min. @ 115V/230Vac input (@25%, 50%, 75% and 100% of max load)

2.5. Energy Consumption

5V only: Input Voltage 115Vac 60Hz/230Vac 50Hz, Energy Consumption $\leq 0.075W$.

2.6. Power saving requirement

115Vac/60Hz, 230Vac/50Hz: Output 0.25W, AC Power < 0.5W

3. Output Characteristics

3.1. Static Output Characteristics <Vo & R+N>

Output Rate	Rated Load		Output Range	R+N	Remark
	Min. Load	Max. Load			
5.00V	0.0A	3.0A	4.75-5.25V	180mVp-p	
9.00V	0.0A	3.0A	8.55-9.45V	210mVp-p	
12.00V	0.0A	3.0A	11.40-12.60V	250mVp-p	
15.00V	0.0A	3.0A	14.25-15.75V	300mVp-p	
20.00V	0.0A	3.25A	19.00-21.00V	300mVp-p	

Ripple & Noise: Measurement is done by 20MHz bandwidth oscilloscope and the output paralleled a 0.1uF ceramic capacitor and a 47uF electrolysis capacitor. (test under the condition of rated input and rated output)

3.2. Line/ Load Regulation

Output Rate	Load Condition		Line Regulation	Load Regulation	Remark
	Min. Load	Max. Load			
5.00V	0.0A	3.0A	$\pm 3\%$	$\pm 5\%$	
9.00V	0.0A	3.0A	$\pm 3\%$	$\pm 5\%$	
12.00V	0.0A	3.0A	$\pm 3\%$	$\pm 5\%$	

15.00V	0.0A	3.0A	± 3%	± 5%	
20.00V	0.0A	3.25A	± 3%	± 5%	

3.3.Turn - on Delay Time

3S max. @ 115Vac input & 5V only

3.4.Hold-up Time

5mS min. @ 115Vac input & 20V only with full load

3.5.Output Overshoot / Undershoot

10% max. When the power on or off, when it is the full input voltage and full load

3.6.Output Transient Response

(1) For 5V Mode

0~25%, 25%~50%, 50%~75%, 75%~100%.Frequency be operated 100Hz , 2.5A/uS
Vo: 4.75V~5.5V

(2) For 9V Mode

0~25%, 25%~50%, 50%~75%, 75%~100%.Frequency be operated 100Hz , 2.5A/uS
Vo: 8.55V~9.45V

(3) For 12V Mode

0~50%, 50%~100%.Frequency be operated 100Hz , 2.5A/uS
Vo: 11.4V~12.6V

(4) For 15V Mode

0~50%, 50%~100%.Frequency be operated 100Hz , 2.5A/uS
Vo: 14.25V~15.75V

(5) For 20V Mode

0~50%, 50%~100%.Frequency be operated 100Hz , 2.5A/uS
Vout: 19V~21V

4. Protection Requirements

4.1.Over Voltage Protection (auto-recovery)

Output	OVP
5.00V	5.5V~7.5V
9.00V	9.6V~11.7V
12.00V	13.2V~15.6V
15.00V	16.5V~19.5V
20.00V	22V~26V

4.2.Over Current Protection

Output	OCP
5.00V	3.3A~3.9A
9.00V	3.3A~3.9A
12.00V	3.3A~3.9A

15.00V	3.3A~3.9A
20.00V	3.6A~4.2A

4.3.Short Circuit Protection

The input power shall decrease when the output rail short, the power supply shall no damage, and shall be self-recovery when the fault condition is removed.

5. Environment Requirements

5.1.Operating Temperature and Relative Humidity

0°C to +35°C

10%RH to 90%RH

5.2.Storage Temperature and Relative Humidity

-30°C to +80°C

5%RH to 95%RH

5.3.Vibration

10 to 300Hz sweep at a constant acceleration of 1.0G(Breadth: 3.5mm) for 1Hour for each of the perpendicular axes X, Y, Z

5.4.Drop in

Height: 1m; the product should be fell off on the hardwood with the thickness of 20mm, and the hardwood should be put on the base of the cement or on the ground without flexibility. Apply one times on all surfaces, total 6 times. The electric performance and Hi-Pot test must be OK after the drop tests.

6. Reliability Requirements

6.1.Burn-in

The power supply shall be burn-in for 4 Hours under normal input and 80% rated load at 35°C

6.2.MTBF Qualification

The MTBF shall be at least 100,000hours at 25°C, Full load and 115Vax/60Hz input

6.3.E-caps lifetime

The E-caps used in this PSU must be with lifetime of 8,760 hours @25°C @100% load@115Vac/60Hz

7. EMI/EMS Standards

7.1.EMI Standards

FCC Part15 EN55032 EN55035 CNS 15936

7.2.EMS Standards

7-2-1 EN 61000-4-2,electrostatic discharge(ESD) requirement

Discharge characteristic	Test level	Test criteria
Air discharge	+/-15KV	A

Contact discharge	+/-8KV	A
-------------------	--------	---

7-2-2 EN 61000-4-3, radiated electromagnetic field susceptibility(rs)

Test level	Test criteria
3V/m (r.m.s)	A
80-1000MHz,80%AM(1KHz) sine-wave	

7-2-3 EN 61000-4-4, electric fast transients(burst) immunity requirement

Coupling	Test level	Test criteria
AC-input	+/-0.5KV	B
AC-input	+/-1KV	B

7-2-4 EN 61000-4-5, surge capability requirement

Surge voltage	Test criteria
Common mode +/-2KV	A
Differential mode +/-1KV	

7-2-5 EN 61000-4-6, Induced radio frequency fields conducted disturbances
Immunity requirement

Test level	Test criteria
3V	A
0.15-80 MHz,80%AM(1KHz)	

7-2-6 Assessment criteria

Acceptance criteria	Performance
A	Agreed operational behavior within the specified limits
B	Time limited functional diminishment or malfunction during the tests is permitted. The function is self-reactivated by the unit following completion of the tests.
C	Malfunction is permitted .The function can be reactivated either by reconnection to the mains or by operator intervention.

8. Safety Standards

8.1.Dielectric Strength(Hi-pot)

Primary to Secondary: 3000Vac / 10mA Max / 60 second (when safety testing).

Primary to Secondary:3000Vac / 5mA Max /3S (when production).

8.2.Leakage Current

0.25mA max. at 264Vac / 50Hz


8.3. Insulation Resistance

100MΩ min. at primary to secondary add 500Vdc test voltage

8.4. Regulatory Standards

Type	Country	Standard	Statue	Mark
UL	USA	UL62368-1	APPROVAL	
CE	Europe	EN62368-1	APPROVAL	
EAC	Russia	IEC62368-1	APPROVAL	
BSMI	China taiwan	CNS15598-1	APPROVAL	

9. Mechanical Outline Drawing



Case material: PC temperature resistance: 120°C

PC+ABS temperature resistance: 95°C

Remark: 1) PC material compliances with ball pressure testing requirement.


2) The colour of Case is black.

10. I/O Marking Drawing



Remark:


1. Material: 100#PET+防刮花fog film(雾膜)
 2. Color: white words with Black ground(黑底白字)
 3. Adhesively
 4. The size of garbage bin is no less than 7mm
 5. The dimension of CE mark can NOT less than 5mm.
- REACH, HSF and conform to MOSO
Renviroment Protection Request
背胶耐温90°C, 96h内不翘角, 不脱落, 不起泡.



备注:


1. 材质:PET
2. 白底黑字(公司内部打印)
3. 条码类型:CODE 128
4. 共用料号:323020002

11. Package Drawing




Packing Instruction:

- 1、the product put in the bag , then the packing product put in the partitioning card groove. 21PCS/floor, 5 floors in all. 105PCS/box such as: 21pcs/floor*5floor=105PCS/box
- 2、the usage of the packing materials:
 - 1) the usage of the four partitioning card 435*375*55: 5PCS
 - 2) the usage of the PE bag 250*120: 105PCS
 - 3) the usage of the flat 435*375:6PCS
 - 4) carton box 450*390*335: 1PCS
- 3、Pallet stacke instruction:
 - 1) Pallet size is:L1200*W950*H135mm
 - 2) per floor set 6pcs
 - 3) stacke per 4floor*6pcs carton total 24 pcs carton




450*390*335MM

the bag of outside size: 450L*390W*335H



The pallet stack drawing



The product will be packed in the carton box and the box will be sealed by the sticker


The requirement of PE bag packing: PE bag without sealing by adhesive tape.

PE bag with sealing by adhesive tape

Other requirement

Remark: If the customer has not chose the PE bag packing way, we will use the PE bag without sealing by adhesive tape.

Carton label



技术要求:

1. 材质: 80P铜版纸 (来料为空白标签)
2. 颜色: 白底黑字, 公司内部打印
3. 背附胶, 粘贴在纸箱上后, 无翘边等不良;
4. 符合ROHS标准及茂硕环保要求
5. 使用空白料号3230200011