

## SPECIFICATION FOR REFERENCE

CUSTOMER: \_\_\_\_\_

CUSTOMER P.N.: \_\_\_\_\_

MODEL NO.: \_\_\_\_\_ **MS-Z5000R120-065D0-Q** \_\_\_\_\_

PRODUCT NO.: \_\_\_\_\_ **SCXXX-Q0/XXXXXX** \_\_\_\_\_

SAMPLE DATE: \_\_\_\_\_ **2023-09-20** \_\_\_\_\_

CUSTOMER AUTHORIZED SIGNATURE		

Please return to us one copy of "SPECIFICATION FOR APPROVAL"  
with you approved signature.

**ADD: MOSO Industrial Park, Nanshan District, Shenzhen, Guangdong  
518108, P. R. China**

**TEL: 86-755-27657000 27657555**

**P.C.: 518108**

**FAX: 86-755-27657908**

**E-mail: [moso@mosopower.com](mailto:moso@mosopower.com)**

**<http://www.mosopower.com>**

Prepared By :	Checked By :	Safetied By:	Approved By :



## ---Table of Content---

1. SCOPE.....	4
1.1. Description.....	4
2. Input Characteristics.....	4
2.1. Input Voltage & Frequency.....	4
2.2. Input AC Current.....	4
2.3. Inrush Current (cold start).....	4
2.4. Averaged Efficiency.....	4
2.5. Energy Consumption.....	4
3. Output Characteristics.....	4
3.1. Static Output Characteristics <Vo & R+N>.....	4
3.2. Line/ Load Regulation.....	4
3.3. Turn - on Delay Time.....	4
3.4. Hold-up Time.....	5
3.5. Rise Time.....	5
3.6. Fall Time.....	5
3.7. Output Overshoot / Undershoot.....	5
3.8. Output Load Transient Response.....	5
4. Protection Requirements.....	5
4.1. Over Current Protection.....	5
4.2. Short Circuit Protection.....	5
4.3. Over Voltage Protection.....	5
5. Environment Requirements.....	5
5.1. Operating Temperature and Relative Humidity.....	5
5.2. Storage Temperature and Relative Humidity.....	5
5.3. Altitude:Sea level to 5,000 meters.....	5
5.4. Vibration.....	5
5.5. Drop Test.....	6
6. Reliability Requirements.....	6
6.1. Burn-in.....	6
6.2. MTBF.....	6
6.3. E-caps lifetime.....	6
7. EMI/EMS Standards.....	6
7.1. EMI Standards.....	6
7.2. EMS Standards.....	6
8. Safety Standards.....	7
8.1. Dielectric Strength (Hi-pot).....	7
8.2. Leakage Current.....	7

8.3. Insulation Resistance .....	7
8.4. Regulatory Standards .....	7
9. Mechanical Outline Drawing .....	8
10. I/O Marking Drawing .....	9
11. Package Drawing .....	10

## 1. SCOPE

The document detail the electrical, mechanical and environmental specifications of a SMPS, the power supply provide 60W continuous output power.

The power supply shall meet the **HSF** requirement.

### 1.1. Description

- SMPS Adaptor(Wall mount)
  SMPS Adaptor(Desk-top)
- Open Frame
  SMPS Unit (With Case)
- Others

## 2. Input Characteristics

### 2.1. Input Voltage & Frequency

The range of input voltage is from 90Vac to 264Vac single phase.

	Minimum	Nominal	Maximum
Input Voltage	90Vac	100Vac~240Vac	264Vac
Input Frequency	47Hz	50Hz/60Hz	63Hz

### 2.2. Input AC Current

1.8A max. @ 100-240Vac input & Full load.

### 2.3. Inrush Current (cold start)

No damage shall be presented at the cold start

### 2.4. Averaged Efficiency

88% min. @ 115/230Vac 60Hz input (@25%, 50%, 75% and 100% of max load)

### 2.5. Energy Consumption

No load Consumption  $\leq 0.21W$ (115Vac/60Hz, 230Vac/50Hz)

## 3. Output Characteristics

### 3.1. Static Output Characteristics <Vo & R+N>

Output Rate	Rated Load		Output Range	R+N	Remark
	Min. Load	Max. Load			
+12.0V	0.0A	5A	11.4V~ 12.6V	150mVp-p	100-240V

Ripple & Noise: Measurement is done by 20MHz bandwidth oscilloscope and the output paralleled a 0.1uF ceramic capacitor and a 22uF electrolytic capacitor. (test under the condition of rated input and rated output).

### 3.2. Line/ Load Regulation

Output Rate	Load Condition		Line Regulation	Load Regulation	Remark
	Min. Load	Max. Load			
+12.0V	0.0A	5A	$\pm 2\%$	$\pm 5\%$	

### 3.3. Turn - on Delay Time

3S max. @ 100Vac to 240Vac input & Full load.

### 3.4. Hold-up Time

10mS min. @ Full load & 115Vac/60Hz input turn off at worst case.

20mS min. @ Full load & 230Vac/50Hz input turn off at worst case.

### 3.5. Rise Time

50mS max. @ Rated load.

### 3.6. Fall Time

30mS max. @ Full load.

### 3.7. Output Overshoot / Undershoot

10% max. When the power on or off, when it is the full input voltage and full load

### 3.8. Output Load Transient Response

Output voltage within 11.4-12.6V for load step from 20% to 80%, R/S: 0.1A/uS,

Frequency: 100Hz duration and 8mS at 80%.

## 4. Protection Requirements

### 4.1. Over Current Protection

Over Current Point Limited:  $I > 5.5A$  (100-240Vac)

The output shall hiccup when the over current applied to the output rail, and shall be self-recovery when the fault condition is removed.

### 4.2. Short Circuit Protection

The input power shall decrease when the output rail short, the power supply shall no damage, and shall be self-recovery when the fault condition is removed.

### 4.3. Over Voltage Protection

The power supply has to be protected against over voltage conditions. No damage allowed. The power supply must come back to nominal working without on/off powering after removal of the over voltage condition.

## 5. Environment Requirements

### 5.1. Operating Temperature and Relative Humidity

→ -20°C ~ +45°C @ 100% load ∈ (90Vac, 264Vac)

0°C ~ +55°C @ 90% load ∈ (90Vac, 264Vac)

Note: PSU can start-up at -30°C @ 60% load / -20°C @ 100% load (Input voltage: 90V, 264Vac)

### 5.2. Storage Temperature and Relative Humidity

-40°C to +70°C

5%RH to 95%RH

### 5.3. Altitude: Sea level to 5,000 meters.

### 5.4. Vibration

10 to 300Hz sweep at a constant acceleration of 1.0G (Breadth: 3.5mm) for 1Hour for each of the perpendicular axes X, Y, Z.

### 5.5. Drop Test

Height: 1m; the product should be fell off on the hardwood with the thickness of 20mm.  
Apply one time on all surfaces, totally 6 surfaces. The electric performance and Hi-Pot test must be OK after the drop tests.

## 6. Reliability Requirements

### 6.1. Burn-in

The power supply shall be burn-in for 2 Hours under normal input and 80% rated load at 40°C ± 5°C. the electric performance and Hi-Pot test must be OK.

### 6.2. MTBF

The MTBF of power supply shall be over than 50,000 Hours @ 25°C 100% Load & 115Vac/230Vac input.

### 6.3. E-caps lifetime

The E-caps used in this PSU must be with lifetime of 3 years @25°C@100% load@ 115Vac/60Hz、230Vac/50Hz Input.

## 7. EMI/EMS Standards

### 7.1. EMI Standards

GB/T9254 GB17625.1 FCC Part15 EN55032 EN55035

### 7.2. EMS Standards

7-2-1 EN 61000-4-2, electrostatic discharge(ESD) requirement

Discharge characteristic	Test level	Test criteria
Air discharge	+/-8KV	A
Contact discharge	+/-6KV	A

7-2-2 EN 61000-4-3, radiated electromagnetic field susceptibility(rs)

Test level	Test criteria
3V/m (r.m.s)	A
80-1000MHz,80%AM(1KHz) sine-wave	

7-2-3 EN 61000-4-4, electric fast transients(burst) immunity requirement

Coupling	Test level	Test criteria
AC-input	1KV	B
AC-input	1KV	B

7-2-4 EN 61000-4-5 ,surge capability requirement

Surge voltage	Test criteria
Common mode +/-2KV	A
Differential mode +/-1KV	

7-2-5 EN 61000-4-6, Induced radio frequency fields conducted disturbances immunity requirement

Test level	Test criteria
3V	A
0.15-80 MHz, 80%AM(1KHz)	

7-2-6 Assessment criteria

Acceptance criteria	performance
A	Agreed operational behavior within the specified limits
B	Time limited functional diminishment or malfunction during the tests is permitted. The function is self-reactivated by the unit following completion of the tests.
C	Malfunction is permitted. The function can be reactivated either by reconnection to the mains or by operator intervention.

## 8. Safety Standards

### 8.1. Dielectric Strength (Hi-pot)

Primary to Secondary: 3000Vac / 10mA max. / 60second(when safety testing).

Primary to Secondary: 3300Vac / 5mA max. / 3S for production.

### 8.2. Leakage Current

3.5mA max. at 264Vac / 60Hz.


### 8.3. Insulation Resistance

100MΩ min. at primary to secondary add 500Vdc test voltage.

### 8.4. Regulatory Standards

Type	Country	Standard	Statue	Mark
CCC	China	GB4943.1	APPROVAL	
CE	Europe	EN62368-1	APPROVAL	
UKCA	UK	EN62368-1	APPROVAL	
UL	USA	UL62368-1	APPROVAL	

## 9. Mechanical Outline Drawing




Case material:  PC temperature resistance: 125°C.

PC+ABS temperature resistance: 95°C.

Remark: 1) PC material compliances with ball pressure testing requirement.


2) The color of the casing and DC cable is black(1101M).

### 10. I/O Marking Drawing




**Remark:**

1. Above lable is laser engraved.
2. The dimension of garbage bin mark can NOT less than 7mm.
3. The dimension of CE mark and UKCA mark can NOT less than 5mm.




- product code(产品编码:实际S编码后六位, 如SC516-Q0, 取C516Q0)
- producing year(产品实际生产年份,年份最后一位, 如2023年, 取3)
- producing month(产品实际生产月份, 如11月, 取11)
- producing date(产品实际生产日期, 如12日, 取12)
- product listing number(产品序列号, 000001-999999)

## 11. Package Drawing






### Packing Instruction:


- 一、the product put in the PE bag ,  
then the packing product put in the  
partitioning card groove. 25PCS/floor,  
2 floors in all, 50PCS/box  
such as: 25pcs/floor\*2floor=50PCS/box
- 二、the usage of the packing materials:
  - 1、the usage of the six partitioning card A 326\*140: 12PCS (K3K)
  - 2、the usage of the six partitioning card B 376\*140: 12PCS (K3K)
  - 3、the usage of the PE bag 250\*120: 50PCS
  - 4、the usage of the flat 376\*326: 3PCS (K3K)
  - 5、carton box 390\*340\*310: 1PCS (K=K)
- 三、Pallet stacke instruction:
  - 1、Pallet size is:L1200\*W800\*H135mm
  - 2、per floor set 6pcs
  - 3、stacke per 4floor\*6pcs carton  
total 24 pcs carton



The pallet stack drawing



CARTON BOX: 390L \*340W\*310H



The product will be packed in the carton box  
and the box will be sealed by the sticker

- The requirement of PE bag packing:  PE bag without sealing by adhesive tape.  
 PE bag with sealing by adhesive tape  
 Other requirement

Remark: If the customer has not chose the PE bag packing way,  
we will use the PE bag without sealing by adhesive tape.