

参考规格书

SPECIFICATION FOR REFERENCE

CUSTOMER/客户: _____

CUSTOMER P.N./客户物料号: _____

MODEL NO./产品型号: A30-Z4740R190-090G0-E

PRODUCT NO./产品编号: SCXXX-E0/XXXXXX

SAMPLE DATE/送样日期: 2023-11-03

CUSTOMER AUTHORIZED SIGNATURE/客户承认签核		

Please return to us one copy of "SPECIFICATION FOR APPROVAL"
with you approved signature./客户确认签字,
盖章后请回传一份承认书给我司.

ADD: MOSO Industrial Park, Nanshan District, Shenzhen, Guangdong
518108, P. R. China

地址:深圳市南山区茂硕科技园

TEL: 86-755-27657000 27657555

P.C.: 518108

FAX: 86-755-27657908

E-mail:moso@mosopower.com

<http://www.mosopower.com>

拟 制:	项目工程师:	安规工程师:	批 准:

**** Table Of Content/目录 ****

1.	SCOPE	4
1.1.	Description	4
2.	Input Characteristics/输入特性	4
2.1.	Input Voltage & Frequency/输入电压与频率	4
2.2.	Input AC Current/AC 输入电流	4
2.3.	Inrush Current (cold start)/浪涌电流(冷启动)	4
2.4.	Averaged Efficiency/平均效率	4
2.5.	Energy Consumption /空载功耗	4
3.	Output Characteristics/输出特性	4
3.1.	Static Output Characteristics <Vo & R+N>/静态输出特性	4
3.2.	Line/ Load Regulation/线性/负载调整率	5
3.3.	Turn - on Delay Time/开机延迟时间	5
3.4.	Hold-up Time/关机维持时间	5
3.5.	Rise Time/上升时间	5
3.6.	Fall Time/下降时间	5
3.7.	Output Overshoot / Undershoot/输出过冲/欠冲	5
3.8.	Output Load Transient Response/输出负载瞬态响应	5
4.	Protection Requirements/保护要求	5
4.1.	Over Current Protection/过流保护	5
4.2.	Short Circuit Protection/短路保护	5
4.3.	Over Voltage Protection/过压保护	5
5.	Environment Requirements/环境要求	6
5.1.	Operating Temperature and Relative Humidity/操作温/湿度要求	6
5.2.	Storage Temperature and Relative Humidity/存储温/湿度要求	6
5.3.	Vibration/振动	6
6.	Reliability Requirements/可靠性要求	6
6.1.	Burn-in/煲机	6
6.2.	MTBF/平均失效时间	6
6.3.	E-caps lifetime/电容寿命	6
7.	EMI/EMS Standards/EMI/EMS 标准	6
7.1.	EMI Standards/EMI 标准	6
7.2.	EMS Standards/EMS 标准	6
8.	Safety Standards/安规标准	8
8.1.	Dielectric Strength(Hi-pot)/介电耐压强度(高压)	8
8.2.	Leakage Current/漏电流	8
8.3.	Insulation Resistance/绝缘阻抗	8
8.4.	Earthing Resistance/接地阻抗测试	8

8.5.	Regulatory Standards/安规标准.....	8
9.	Mechanical Outline Drawing/外观示意图.....	9
10.	I/O Marking Drawing/铭牌示意图.....	10
11.	Package Drawing/包装示意图.....	11

1. SCOPE

The document detail the electrical, mechanical and environmental specifications of a SMPS, the power supply provide 90W continuous output power.

资料详细描述了一款 90 W (连续输出功率)开关电源的电气性,结构性及环境等要求.

The power supply shall meet the **HSF** requirement.

此款电源符合 **HSF** 要求.

1.1. Description

- SMPS Adaptor(Wall mount)/插墙式适配器 SMPS Adaptor(Desk-top)/桌面型适配器
 Open Frame/开放式结构 SMPS Unit (With Case)/带铁壳型
 Others/其他

2. Input Characteristics/输入特性

2.1. Input Voltage & Frequency/输入电压与频率

The range of input voltage is from 90Vac to 264Vac single phase.

输入电压范围: 从 **90Vac** 到 **264Vac**, 单相输入.

	Minimum/最小	Nominal/额定值	Maximum/最大
Input Voltage/输入电压	90Vac	100 Vac~ 240 Vac	264Vac
Input Frequency/输入频率	47 Hz	60 Hz/ 50Hz	63Hz

2.2. Input AC Current/AC 输入电流

1.8A max. @ 100-240Vac input & Full load.

输入电压 **100-240Vac** 满载时, 输入电流不超过 **1.8A**。

2.3. Inrush Current (cold start)/浪涌电流(冷启动)

The energy of inrush current should not be over the I²T of fuse & bridge diodes.

冷启动时, 浪涌能量不能超过整流桥和保险丝的 I²T, 且不能有损坏.

2.4. Averaged Efficiency/平均效率

88% min. @115Vac/60Hz, 230Vac/50Hz input (@25%, 50%, 75% and 100% of max load)

输入电压 **115V/60Hz**, **230V/50Hz** 时, **25%**、**50%**、**75%**和 **100%**载时的平均效率不低于 **88%**

2.5. Energy Consumption /空载功耗

No load Consumption ≤0.21W(**115V/60Hz**, **230V/50Hz**).

在额定输入 **115V/60Hz**, **230V/50Hz** 时,空载功耗≤**0.21W**.

3. Output Characteristics/输出特性

3.1. Static Output Characteristics <Vo & R+N>/静态输出特性

Output Rate	Rated Load/额定负载		Output Range 输出电压范围	R+N 纹波与噪声	Remark 备注
	Min. Load	Rate.Load			
+19V	0.0A	4.74A	18.05V ~ 19.95V	250mVp-p	100-240V

Ripple & Noise: Measurement is done by 20MHz bandwidth oscilloscope and the output paralleled a 0.1uF ceramic capacitor and a 47uF electrolytic capacitor. (test under the condition of rated input and rated output).

纹波与噪声: 量测时示波器选用 20MHz 带宽限制,输出端要并联一颗 0.1uF 的陶瓷电容和一颗 47uF 的电解电容. (在额定输入及输出的条件下检测).

3.2. Line/ Load Regulation/线性/负载调整率

Output	Load Condition/负载条件		Line Regulation	Load Regulation	Remark
Rate	Min. Load	Rate.Load	线性调整率	负载调整率	备注
+19V	0.0A	4.74A	± 3%	± 5 %	

3.3. Turn - on Delay Time/开机延迟时间

3S max. @90Vac to 264Vac input & Full load.

输入电压 90Vac to 264Vac 满载时, 开机延迟时间不超过 3S。

3.4. Hold-up Time/关机维持时间

5mS min. @ Full load & 115Vac/60Hz input turn off at worst case

输入电压 115Vac/60Hz 满载时, 关机时间最差情况不小于 5 毫秒。

3.5. Rise Time/上升时间

50 mS max. @ Rated load.

额定负载时, 上升时间不超过 50 毫秒。

3.6. Fall Time/下降时间

50 mS max. @ Full load.

满载时, 下降时间不超过 50 毫秒。

3.7. Output Overshoot / Undershoot/输出过冲/欠冲

10 % max. When the power on or off, when it is the full input voltage and full load.

开关机时, 输出过冲/欠冲均不大于 10%。

3.8. Output Load Transient Response/输出负载瞬态响应

Output voltage within 18.05V~19.95V for load step from 20% to 80%, R/S: 0.25A/uS, Frequency: 100Hz , 50%duty.

输出电压在 18.05V~19.95V 范围内, 负载阶跃为 20%至 80%, R / S: 0.25A / uS,

频率: 100Hz, 50% 占空比

4. Protection Requirements/保护要求

4.1. Over Current Protection/过流保护

Over Current Point Limited/过流点限制: $I > 5.2A$ (100-240Vac)

The output shall hiccup when the over current applied to the output rail, and shall be auto-recovery when the fault condition is removed.

当过电流时,输出将进入打嗝模式,当过流情况解除后,产品将会自动恢复正常。

4.2. Short Circuit Protection/短路保护

The input power shall decrease when the output rail short, the power supply shall no damage, and shall be auto-recovery when the fault condition is removed.

当输出短路时,产品输入功率降低且不会损伤,当短路情况解除后,产品将会自动恢复正常。

4.3. Over Voltage Protection/过压保护

The power supply has to be protected against over voltage conditions. No damage allowed. The power supply must come back to nominal working without on/off powering

after removal of the over voltage condition.当过压保护时,产品输出功率不会损伤,当过压情况解除后,产品恢复正常.

5. Environment Requirements/环境要求

5.1. Operating Temperature and Relative Humidity/操作温/湿度要求

0°C to +40°C

10%RH to 90%RH

5.2. Storage Temperature and Relative Humidity/存储温/湿度要求

-20°C to +70°C

5%RH to 95%RH non-condensing @ Sea level shall be low 5,000 meters/低于 5,000 米.

5.3. Vibration/振动

10 to 300Hz sweep at a constant acceleration of 1.0G(Breadth: 3.5mm) for 1Hour for each of the perpendicular axes X, Y, Z.

扫描频率: 10 to 300Hz, 加速度: 1.0G(位移: 3.5mm), X, Y, Z 三垂直坐标轴向各振动 1 小时.

6. Reliability Requirements/可靠性要求

6.1. Burn-in/煲机

The power supply shall be burn-in for 2 Hours under normal input and 80% rated load at 40°C ± 5°C, the electric performance and Hi-Pot test must be OK.

电源应在正常输入和 40°C ± 5°C 的 80% 额定负载下老化 2 小时, 电性能和 Hi-Pot 测试必须正常。

6.2. MTBF/平均失效时间

The MTBF of power supply shall be over than 300,000 Hours @ 25°C 100%Load

平均间隔故障时间: 在 25°C, 100% 负载条件下, 至少工作 300,000 小时.

6.3. E-caps lifetime/电容寿命

The E-caps used in this PSU must be with lifetime of 2 Years @ 25°C under 100% load and 115V/230VAC input condition.

在 25 度环境下, 满载和 115V/230VAC 输入电压, 电容寿命至少达 2 年。

7. EMI/EMS Standards/EMI/EMS 标准

7.1. EMI Standards/EMI 标准

FCC Part15 Class B EN55032 EN55035

7.2. EMS Standards/EMS 标准

7-2-1 EN 61000-4-2, electrostatic discharge(ESD) requirement/静电抗扰度要求

Discharge characteristic/静电规格	Test level/测试条件	Test criteria/测试标准
Air discharge/空气放电	+/- 8KV	A
Contact discharge/接触放电	+/- 4KV	A

7-2-2 EN 61000-4-3, radiated electromagnetic field susceptibility(rs)/辐射骚扰场强

Test level/测试条件	Test criteria/测试标准
3V/m (r.m.s)	A
80-1000MHz, 80%AM(1KHz) sine-wave	

7-2-3 EN 61000-4-4,electric fast transients(burst) immunity requirement/电快速瞬变脉冲群

Coupling/测试端口	Test level/测试条件	Test criteria/测试标准
AC-input/交流输入	1KV	A
AC-input/交流输入	2KV	B

7-2-4 EN 61000-4-5,surge capability requirement/浪涌抗扰度要求

Surge voltage/雷击电压	Test criteria/测试标准
Common mode/共模 +/- 4KV	A
Differential mode/差模 +/-4KV	

7-2-5 EN 61000-4-6, Induced radio frequency fields conducted disturbances immunity requirement/电源端子传导骚扰实验

Test level/测试条件	Test criteria/测试标准
3V	A
0.15-80 MHz,80%AM(1KHz)	

7-2-6 Assessment criteria /评估标准

Acceptance criteria 可接受标准	Performance 性能
A	Agreed operational behavior within the specified limits 性能不允许变化; 如果性能会发生变化, 则变化的范围在产品规格书规定的范围内.
B	Time limited functional diminishment or malfunction during the tests is permitted. The function is self-reactivated by the unit following completion of the tests. 设备在测试过程中,性能降低允许在产品规格书要求范围内,干扰消除后,设备能恢复正常,不允许出现复位和任何方式的人工干预.
C	Malfunction is permitted .The function can be reactivated either by reconnection to the mains or by operator intervention. 在测试过程中, 设备允许出现业务中断, 测试完毕后允许自行恢复或者人工干预恢复(包括硬件上干预); 测试中只允许初级防护器件损坏, 并且更换损坏的初级防护器件后, 设备能恢复正常

8. Safety Standards/安规标准

8.1. Dielectric Strength(Hi-pot)/介电耐压强度(高压)

Primary to Secondary: 1500Vac / 10mA max. / 60 second.

初级对次级: **1500Vac / 10mA max./ 60 秒(安规试验)** .

Primary to Secondary: 1800Vac / 5mA max. / 3 S.

初级对次级: **1800Vac / 5mA max. / 3S(生产作业)**.

8.2. Leakage Current/漏电流

0.5mA max. at 264Vac / 60Hz.

8.3. Insulation Resistance/绝缘阻抗

50MΩ min. at primary to secondary add 500Vdc test voltage.

在初级与次级间加 **500Vdc** 进行测试


8.4. Earthing Resistance/接地阻抗测试

Earthing Resistance: <0.1 Ω at 12VDC/25A/1S.

8.5. Regulatory Standards/安规标准

Type/安规	Country/国家	Standard/标准	State/状况	
UL	USA	UL62368-1	APPROVAL	
CE	Europe	EN62368-1	APPROVAL	

9. Mechanical Outline Drawing/外观示意图




- 外壳材质: PC 耐温: 120°C
 PC+ABS 耐温: 95°C
 备注: 1) PC 材质符合球压测试要求.
 2) 外壳与线材为黑色 (1101M) .

10. I/O Marking Drawing/铭牌示意图




Remark:

1. Above label is laser engraved.
2. The dimension of garbage bin mark can NOT less than 7mm.







- product code(产品编码:实际S编码后六位, 如SC606-E0, 取C606E0)
- producing year(产品实际生产年份,年份最后一位, 如2023年, 取3)
- producing month(产品实际生产月份, 如11月, 取11)
- producing date(产品实际生产日期, 如12日, 取12)
- product listing number(产品序列号, 000001-999999)

11. Package Drawing/包装示意图




Packing Instruction:

- 1、the product put in the bag , then the packing product put in the partitioning card groove . 8PCS/floor, 4 floors in all , 32PCS/box
such as: 8pcs/floor*4floor=32PCS/box
- 2、the usage of the packing materials:
 - 1) Combined knife card dosage: 485*385*70 4PCS
 - 3) the usage of the PE bag 250*140: 32PCS
 - 4) the usage of the flat 485*385: 5PCS
 - 5) carton box 500*400*335: 1PCS
- 3、Pallet stacke instruction:
 - 1) Pallet size is: L1000*W800*H100mm
 - 2) per floor set 4pcs
 - 3) stacke per 4floor*4pcs carton total 16 pcs carton




500*400*335MM

the bag of outside size: 500L*400W*335H



The pallet stack drawing



The product will be packed in the carton box and the box will be sealed by the sticker

- PE 袋包装要求: PE 袋不用胶带封口;
 PE 袋用胶带封口;
 其它要求;

备注: 若客户未进行选择 PE 袋包装要求或备注时, 我司默认采用 PE 袋不用胶带封口包装方式