

参考规格书

SPECIFICATION FOR REFERENCE

CUSTOMER/客户: _____

CUSTOMER P.N./客户物料号: _____

MODEL NO./产品型号: V30-Z2000R240-048F0-E

PRODUCT NO./产品编号: SCXXX-E0/XXXXXX

SAMPLE DATE/送样日期: 2022-11-25

CUSTOMER AUTHORIZED SIGNATURE/客户承认签核		

Please return to us one copy of "SPECIFICATION FOR APPROVAL"
with you approved signature./客户确认签字,
盖章后请回传一份承认书给我司.

ADD: MOSO Industrial Park, Nanshan District, Shenzhen, Guangdong
518108, P. R. China

地址: 深圳市南山区茂硕科技园

TEL: 86-755-27657000 27657555

P.C.: 518108

FAX: 86-755-27657908

E-mail: moso@mosopower.com

<http://www.mosopower.com>

拟 制:	项 目 工 程 师:	安 规 工 程 师:	批 准:

**** Table Of Content/目录 ****

1. SCOPE/简述	4
1.1. Description.....	4
2. Input Characteristics/输入特性.....	4
2.1. Input Voltage & Frequency/输入电压与频率.....	4
2.2. Input AC Current/AC 输入电流.....	4
2.3. Inrush Current (cold start)/浪涌电流(冷启动).....	4
2.4. Averaged Efficiency/平均效率	4
2.5. Energy Consumption /空载功耗	4
3. Output Characteristics/输出特性	5
3.1. Static Output Characteristics <Vo & R+N>/静态输出特性.....	5
3.2. Line/ Load Regulation/线性/负载调整率	5
3.3. Turn - on Delay Time/开机延迟时间.....	5
3.4. Hold-up Time/关机维持时间	5
3.5. Rise Time/上升时间.....	5
3.6. Fall Time/下降时间.....	5
3.7. Output Overshoot / Undershoot/输出过冲/欠冲.....	5
3.8. Output Load Transient Response/输出负载瞬态响应.....	5
4. Protection Requirements/保护要求.....	6
4.1. Over Current Protection/过流保护	6
4.2. Short Circuit Protection/短路保护	6
4.3. Over Voltage Protection/过压保护	6
5. Environment Requirements/环境要求.....	6
5.1. Operating Temperature and Relative Humidity/操作温/湿度要求.....	6
5.2. Storage Temperature and Relative Humidity/存储温/湿度要求	6
5.3. Vibration/振动.....	6
5.4. Drop Test	6
6. Reliability Requirements/可靠性要求.....	6
6.1. Burn-in/老化	6
6.2. MTBF/平均失效时间	7
6.3. E-caps lifetime/电容寿命.....	7
7. EMI/EMS Standards/EMI/EMS 标准	7
7.1. EMI Standards/EMI 标准	7
7.2. EMS Standards/EMS 标准.....	7
8. Safety Standards/安规标准	8
8.1. Dielectric Strength(Hi-pot)/介电耐压强度(高压)	8
8.2. Leakage Current/漏电流.....	8
8.3. Insulation Resistance/绝缘阻抗.....	8

8.4. Regulatory Standards/安规标准	8
9. Mechanical Outline Drawing/外观示意图	9
10. I/O Marking Drawing/铭牌示意图	10
11. Package Drawing/包装示意图	11

1. SCOPE/简述

The document details the electrical, mechanical and environmental specifications of a SMPS, the power supply provide 48W continuous output power.

资料详细描述了一款 **48W** 连续输出功率开关电源的电气性,结构性及环境等要求.

The power supply shall meet the RoHS requirement.

此款电源符合 **RoHS** 要求.

1.1. Description

- SMPS Adaptor(Wall mount)/插墙式适配器 SMPS Adaptor(Desk-top)/桌面型适配器
 Open Frame/开放式结构 SMPS Unit (metal Case)/带铁壳型
 Others/其他

2. Input Characteristics/输入特性

2.1. Input Voltage & Frequency/输入电压与频率

The range of input voltage is from 90Vac to 264Vac single phase.

输入电压范围: 从 **90Vac** 到 **264Vac**, 单相输入.

	Minimum/最小	Nominal/额定值	Maximum/最大
Input Voltage/输入电压	90Vac	100Vac-240Vac	264Vac
Input Frequency/输入频率	47Hz	50Hz /60Hz	63Hz

2.2. Input AC Current/AC 输入电流

1.3A max. @ 100-240Vac input & Full load.

输入电压 **100-240Vac** 满载时, 输入电流不超过 **1.3A**。

2.3. Inrush Current (cold start)/浪涌电流(冷启动)

100A max. @ 230Vac input.

输入电压 **230Vac** 时, 输入电流不超过 **100A**。

2.4. Averaged Efficiency/平均效率

87.77% min. @ 115Vac input (@25%, 50%, 75% and 100% of max. load).

输入电压 **115V/60Hz** 时, **25%、50%、75%和 100%**载时的平均效率不低于 **87.77%**。

88.97% min. @ 230Vac input (@25%, 50%, 75% and 100% of max. load).

输入电压 **230V/50Hz** 时, **25%、50%、75%和 100%**载时的平均效率不低于 **88.97%**。

2.5. Energy Consumption /空载功耗

No load Consumption $\leq 0.1W$ (115Vac/60Hz).

输入电压 **115Vac/60Hz** 时,空载功耗均小于 **0.1W**。

No load Consumption $\leq 0.075W$ (230Vac/50Hz).

输入电压 **230Vac/50Hz** 时,空载功耗均小于 **0.075W**。

3. Output Characteristics/输出特性

3.1. Static Output Characteristics <Vo & R+N>/静态输出特性

Output Rate	Rated Load/额定负载		Output Range 输出电压范围	R+N 纹波与噪声	Remark 备注
	Min. Load	Max. Load			
+24.0V	0.0A	2.0A	22.8V-25.2V	<240mV	100-240Vac

Ripple & Noise: Measurement is done by 20MHz bandwidth oscilloscope and the output paralleled a 0.1uF ceramic capacitor and a 10uF electrolytic capacitor. (test under the condition of rated input and rated output).

纹波与噪声: 测量时, 示波器选用 **20MHz** 带宽限制, 输出端要并联一颗 **0.1uF** 的陶瓷电容和一颗 **10uF** 的电解电容. (在额定输入及输出的条件下检测)。

3.2. Line/ Load Regulation/线性/负载调整率

Output Rate	Load Condition/负载条件		Line Regulation 线性调整率	Load Regulation 负载调整率	Remark 备注
	Min. Load	Max. Load			
+24.0V	0.0A	2.0A	± 3%	± 5%	

3.3. Turn - on Delay Time/开机延迟时间

3S max. @ 100Vac to 240Vac input & Full load.

输入电压 **100-240Vac** 满载时, 开机延迟时间不超过 **3S**。

3.4. Hold-up Time/关机维持时间

10mS min. @ Full load & 115Vac/60Hz input turn off at the worst case.

输入电压 **115Vac/60Hz** 满载时, 关机时间最差情况不小于 **10** 毫秒。

20mS min. @ Full load & 115Vac/60Hz, 230Vac/50Hz input turn off at the worst case.

输入电压 **230Vac/50Hz** 满载时, 关机时间最差情况不小于 **20** 毫秒。

3.5. Rise Time/上升时间

30mS max. @ Rated load.

额定负载时, 上升时间不超过 **30** 毫秒。

3.6. Fall Time/下降时间

30mS max. @ Full load

满载时, 下降时间不超过 **30** 毫秒。

3.7. Output Overshoot / Undershoot/输出过冲/欠冲

10% max. When the power on or off, when it is the full input voltage and full load.

开关机时, 输入全电压时, 全负载时, 输出电压小于 **10%**。

3.8. Output Load Transient Response/输出负载瞬态响应

Output voltage within 22.8-25.2V for load step from 25% to 50% to 25%, 50% to 75% to 50% R/S: 0.5A/uS, Transient Response Recovery Time :200uS, Dynamic response overshoot ±10%.

输出电压在 **22.8-25.2V** 时, 负载从 **25%到 50%到 25%, 50%到 75%到 50%**, 斜率 **0.5A/uS**, 瞬时响应恢复时间:**200uS**, 动态响应超调**±10%**。

4. Protection Requirements/保护要求

4.1. Over Current Protection/过流保护

Over Current Point Limited/过流点限制: $I > 2.4A$ (100-240Vac)

The output shall hiccup when the over currents applied to the output rail, and shall be self-recovery when the fault condition is removed.

过流时, 输出将进入打嗝模式, 过流情况解除后, 产品将会自动恢复正常。

4.2. Short Circuit Protection/短路保护

The input power shall decrease when the output rail short, the power supply shall no damage, and shall be self-recovery when the fault condition is removed.

当输出短路时, 产品输入功率降低且不会损伤, 当短路情况解除后, 产品将会自动恢复正常。

4.3. Over Voltage Protection/过压保护

The power supply has to be protected against over voltage conditions. No damage allowed. The power supply must come back to nominal working without on/off powering after removal of the over voltage condition.

当过压保护时, 产品输出功率不会损伤, 当过压情况解除后, 产品恢复正常。

5. Environment Requirements/环境要求

5.1. Operating Temperature and Relative Humidity/操作温/湿度要求

0°C to +45°C, 10%RH to 90%RH

温度 0°C 到 +45°C, 湿度 10% RH 到 90% RH。

5.2. Storage Temperature and Relative Humidity/存储温/湿度要求

-20°C to +70°C, 5%RH to 95%RH non-condensing, @ Sea level shall be low 5,000m.

海拔 5,000 米以下, 温度 -20°C 到 +70°C, 湿度 5% RH 到 95% RH

5.3. Vibration/振动

10 to 300Hz sweep at a constant acceleration of 1.0G (Breadth: 3.5mm) for 1Hour for each of the perpendicular axes X, Y, Z.

扫描频率: 10 to 300Hz, 恒定加速度: 1.0G(位移: 3.5mm), X, Y, Z 三垂直坐标轴向各振动 1 小时。

5.4. Drop Test

Height: 1m; the product should be fell off on the hardwood floor with the thickness of 20mm, Apply one time on all surfaces, totally 6 surfaces. The electric performance and safety test after the drop test must be OK.

跌落高度: 1m, 并跌落到厚度为 20mm 的木板上, 每面各 1 次, 共 6 次, 在跌落后电气性能及安全测试 OK..

6. Reliability Requirements/可靠性要求

6.1. Burn-in/老化

The power supply shall be burn-in for 4 Hours under normal input and 80% rated load at 40°C ± 5°C. the electric performance and Hi-Pot test must be OK.

电源在额定输入和 80%负载下, 在 40°C ± 5°C 环境温度下老化 4 小时。

6.2. MTBF/平均失效时间

The MTBF shall be at least 500,000hours at 25°C, Full load and nominal input condition.
平均间隔故障时间: 在 25°C,满载条件下, 至少工作 **50,000** 小时.

6.3. E-caps lifetime/电容寿命

The E-caps used in this PSU must be with lifetime of 1 year at 25°C with 100% load @115Vac/60Hz input ,230Vac/50Hz input.

25°C下, 在 **100%**负载和 **115Vac/60Hz、230Vac/50Hz** 输入条件, 电解电容寿命必须有 **1** 年.

7. EMI/EMS Standards/EMI/EMS 标准

7.1. EMI Standards/EMI 标准

FCC Part15

7.2. EMS Standards/EMS 标准

7-2-1 EN 61000-4-2,electrostatic discharge(ESD) requirement/静电抗扰度要求

Discharge characteristic/静电规格	Test level/测试条件	judgment criteria/评定标准
Air discharge/空气放电	+/-15KV	B
Contact discharge/接触放电	+/-8KV	B

7-2-2 EN 61000-4-3, radiated electromagnetic field susceptibility(rs)/辐射骚扰场强

Test level/测试条件	judgment criteria/评定标准
3V/m (r.m.s)	A
80-1000MHz,80%AM(1KHz) sine-wave	

7-2-3 EN 61000-4-4,electric fast transients(burst) immunity requirement/电快速瞬变脉冲群

Coupling/测试端口	Test level/测试条件	judgment criteria/评定标准
AC-input/交流输入	+/-0.5KV	A
AC-input/交流输入	+/-1KV	A

7-2-4EN 61000-4-5,surge capability requirement/浪涌抗扰度要求

Surge voltage/雷击电压	judgment criteria/评定标准
Common mode/共模 +/-2KV	B
Differential mode/差模 +/-1KV	

7-2-5 EN 61000-4-6, Induced radio frequency fields conducted disturbances immunity requirement/电源端子传导骚扰实验

Test level/测试条件	judgment criteria/评定标准
3V	A
0.15-80 MHz,80%AM(1KHz)	

7-2-6 Assessment criteria /评估标准

Acceptance criteria 可接受标准	Performance 性能
A	Agreed operational behavior within the specified limits 性能不允许变化; 如果性能会发生变化, 则变化的范围在产品规格书规定的范围内.
B	Time limited functional diminishment or malfunction during the tests is permitted. The function is self-reactivated by the unit following completion of the tests. 设备在测试过程中, 性能降低允许在产品规格书要求范围内, 干扰消除后, 设备能恢复正常, 不允许出现复位和任何方式的人工干预.
C	Malfunction is permitted .The function can be reactivated either by reconnection to the mains or by operator intervention. 在测试过程中, 设备允许出现业务中断, 测试完毕后允许自行恢复或者人工干预恢复(包括硬件上干预); 测试中只允许初级防护器件损坏, 并且更换损坏的初级防护器件后, 设备能恢复正常

8. Safety Standards/安规标准

8.1. Dielectric Strength(Hi-pot)/介电耐压强度(高压)

Primary to Secondary: 3000Vac /10mA max. / 60S (when safety testing)

初级对次级: 3000Vac / 10mA max. / 60 秒 (安规试验)

Primary to Secondary: 3300Vac /10mA max. / 3S (when production)

初级对次级: 3300Vac / 10mA max. /3S(生产作业)

8.2. Leakage Current/漏电流

0.25mA max. at 264Vac / 50Hz

8.3. Insulation Resistance/绝缘阻抗


50MΩ min. at primary to secondary add 500Vdc test voltage.

在初级与次级之间加载测试电压 500V 测试, 绝缘阻抗最小 50MΩ.

8.4. Regulatory Standards/安规标准

Type/安规	Country/国家	Standard/标准	State/状况	Note/备注
CCC	China	GB4943.1	APPROVAL	
UL	USA	UL62368-1	APPROVAL	
CE	Europe	EN62368-1	APPROVAL	

9. Mechanical Outline Drawing/外观示意图




外壳材质: ■PC 耐温: 125°C.

□PC+ABS 耐温: 95°C.

备注: 1)PC 材质符合球压测试要求.


2)外壳与线材为黑色.

10. I/O Marking Drawing/铭牌示意图





Remark:

1. Above label is laser engraved.
2. The dimension of garbage bin mark can NOT less than 7mm.




- product code(产品编码:实际S编码后六位, 如SC063-E0, 取C063E0)
- producing year(产品实际生产年份,年份最后一位, 如2022年, 取2)
- producing month(产品实际生产月份, 如11月, 取11)
- producing date(产品实际生产日期, 如12日, 取12)
- product listing number(产品序列号, 000001-999999)

11. Package Drawing/包装示意图




Packing Instruction:


- 一、the product put in the PE bag , then the packing product put in the partitioning card groove, 25PCS/floor, 2 floors in all, 50PCS/box
such as: 25pcs/floor*2floor=50PCS/box
- 二、the usage of the packing materials:
 - 1、the usage of the six partitioning card A 326*140: 12PCS (K3K)
 - 2、the usage of the six partitioning card B 376*140: 12PCS (K3K)
 - 3、the usage of the PE bag 250*120: 50PCS
 - 4、the usage of the flat 376*326: 3PCS (K3K)
 - 5、carton box 390*340*310: 1PCS (K=K)
- 三、Pallet stack instruction:
 - 1、Pallet size is:L1200*W800*H135mm
 - 2、per floor set 6pcs
 - 3、stacke per 4floor*6pcs carton total 24 pcs carton



The pallet stack drawing



CARTON BOX: 390L*340W*310H



The product will be packed in the carton box and the box will be sealed by the sticker

- PE 袋包装要求: PE 袋不用胶带封口;
 PE 袋用胶带封口;
 其它要求;

备注:若客户未进行选择 PE 袋包装要求或备注时,
 我司默认采用 PE 袋不用胶带封口包装方式.